

DECORATIVE BATTENS

INSTALLATION GUIDELINES

Considerations

- Strictly for internal use, not for use in exterior applications, including alfresco areas.
- Should not be used in wet areas such as bathrooms or environments of high humidity.
- inBuilt Decorative Battens are a nonstructural product developed for decorative purposes only.
- Can be cut to length, however, should not be cut in a lineal direction. It is recommended to protect cut edges from moisture ingress.
- Avoid applications where product may be susceptible to high traffic.
- Should not be used where inBuilt Decorative Battens may sit on a floor as wet mopping and vacuum cleaners are likely to cause damage.

Care & Maintenance

- inBuilt Decorative battens are manufactured using decorative overlays. These overlays should be handled with care as a veneered or painted surface would be.
- inBuilt Decorative Battens may be wiped down regularly in the direction of the grain using a damp soapy soft non-abrasive cloth ensuring care is taken not to rub or wipe too hard.
- Dry immediately using a soft cloth so as not to leave any residue on the product.

Fixing

inBuilt does not offer a proprietary fixing system for decorative battens. Subject to your specific application there are many fixing possibilities.

We recommend using a fixing technique or system ordinarily used for natural timber for either wall or ceiling; keeping in mind that MDF/LDF may need to be pre-drilled. You can use Tec7 X-TACK Extreme Bonding Without Support, alongside screw fixing or without.

Note: Flexible adhesive should be applied in a continuous bead along the batten.

When fixing inBuilt battens in a three sided application ensure the decorative joint overlap is facing the ceiling or wall.

NOTE

Do not use any of the following on inBuilt Decorative Battens: Commercial Cleaning Products, Abrasive Cleaners, Scouring Pads or Abrasive Papers, Acids and Alkalis, Solvents, Thinners, Turpentine (Turps), Ammonia mentioned products.